


# U3 Type Crystal



## Features

- U3 typical 11.0x4.6x10.7mm standard footprint.
- High stability and Long-term stability.
- Resistance welding for hermetical seal.
- Tight tolerance 10 ppm available.
- **Lead Free and RoHS compliant**

## ORDERING GUIDANCE

Product Type	Oscillation Mode	Calibration Tolerance (ppm)	Temperature Stability (ppm)	Operation Temp Range (°C)	Load Capacitance (pF)	Frequency (MHz)
Code: Meaning	Code: Meaning	Code: Meaning	Code: Meaning	Code: Meaning	Code: Meaning	
U3: HC-49/UT	1: Fund 3: 3 <sup>rd</sup> OT 5: 5 <sup>th</sup> OT	A: ±10 B: ±15 C: ±20 D: ±30 F: ±50 G: ±5 H: ±25 XX: Special	1: ±10 2: ±15 3: ±20 4: ±30 5: ±50 6: ±100 7: ±5 8: ±3 9: ±25 00: Special	A: -10~+60 B: 0~+70 C: -20~+70 D: -40~+85 E: -55~+125 F: -10~+70 G: -40~+60 H: 0~+60 I: -20~+60 J: -40~+105 K: -40~+70 L: -40~+125	0: Series XX: CL Value In pF	XXX.XXXXXX
<b>Ordering example:</b> U3-1D4C18-20.000000MHz HC-49/UT Fund ±30ppm ±30ppm/-20~+70°C 18pF 20.000000MHz						
<b>Note:</b> If any other requirements are needed, they should be specified in customers' order.						

## Electrical Specification

Storage Temp. Range	-55°C to +125°C
Drive Level(DL)	100uW typ., 500uW
Shunt Capacitance(C0)	7.0pF Max.
Insulation Resistance(IR)	500MΩ Min. @ 100V DC
Aging	±3ppm/year

## Equivalent Series Resistance(ESR)

Frequency (MHz)	Mode	Max ESR (Ohms)
10.000 – 15.999	Fund	30
16.000 – 35.000	Fund	20
25.000 – 100.000	3 <sup>rd</sup> O/T	40
60.000 – 79.999	5 <sup>th</sup> O/T	80
80.000 – 150.000	5 <sup>th</sup> O/T	60

